



Note on global warming and recycling system

Derogar Shahram*

Department of Sustainable Environment and Energy Systems, Middle East Technical University, Guzelyurt, Turkey

*Corresponding author. E-mail: shahram.de.gar@gmail.com

Received: 01-Apr-2022, Manuscript no: GJWSFW-22-64257, **Editor assigned:** 05-Apr-2022, PreQC no: GJWSFW-22-64257 (PQ), **Reviewed:** 20-Apr-2022, QC no: GJWSFW-22-64257, **Revised:** 28-Apr-2022, Manuscript no: GJWSFW-22-64257 (R), **Published:** 06-May-2022, DOI: 10.15651/2449-1780.22.11.005.

DESCRIPTION

Effective techniques to reduce the production of greenhouse gases like carbon dioxide and methane include trash reduction, recycling, and composting. They accomplish this in two ways by helping save energy in the processing of materials for industrial and consumer use. Fresh wood is increasingly being used in industries for a variety of purposes. For example, the paper industry uses it to make newsprint, the plywood industry uses it to make plywood, and the transportation industry uses it to transport goods. Fresh wood is also used to make wood pallets. Wood is used in industries to make packaging accessories such as wooden pallets, wooden crates, and wooden boxes. Generally the wood pallets are used by industries one time only and after that either it used for making furniture or in replace of coal in brick making sector or boiler plants. Indeed high quality of fresh wood like pine wood, hickory wood, red wood etc. used for artificial use and after one time use either it burned or used for making cabinetwork. One of the advantages of reused wood about which generally peoples aren't apprehensive, that most recycled forest land are actually stronger than new wood.

When we manufacture new wood/ timber we need fresh wood and before using it, that wood will placed in a drying furnace to get dry the moistness within wood but it cannot fully remove at all. With recycled wood, that can be sure that the humidity content is nearly zero because it's formerly dry for long time, therefore making them veritably hard and sturdy. Recycled wood has the advantage of lower humidity content about 20% as compared to new wood about 60% to 70%. This means for the same weight of wood purchased you have to pay for less moisture when it comes to recycled wood. The lower humidity content also means advanced continuity. With wood recycling we can reduce the raw material cost as well operation cost. Recycling timber has come popular due to its image as an environmentally friendly product. Common belief

among consumers is that by copping recycled wood, the demand for green timber will fall and eventually profit the terrain. Greenpeace also view recycled timber as an environmentally friendly product, citing it as the most preferable timber source on their website. The appearance of recycled timber as a construction product has been important in both raising assiduity and consumer mindfulness towards deforestation and promoting timber produce to borrow further environmentally friendly practices. Uses for recycled waste wood include traditional feedstock for the panel board assiduity, which still accounts for the maturity of recycled wood, shells, play areas and sludge beds. Old buildings, bridges and marinas, where it is carefully stripped out and put aside by demolishers. At the same time any usable dimension stone is set aside for reuse. The demolishers then sell the salvaged timber to merchants who then re-mill the timber by manually scanning it with a metal detector, which allows the timber to be de-nailed and sawn to size. Once re-milled the timber is commonly sold to consumers in the form of timber flooring, beams and decking. Wood residue used in energy product provides two fold environmental benefits. Originally, its use reduces assiduity reliance on environmentally dangerous reactionary energies, in turn precluding the release of long- term carbon store from sources that cannot be replenished. Secondly, the energy itself omits far smaller hot house gas emigrations than typical druthers. Mango wood, pine, improve wood, birch wood, alder wood, beech wood, poplar wood, fir wood, oak wood, ash wood, hornbeam wood. Use of wood also depend upon the uses of packaging stuff, either packaging made for original transport purpose or for import purpose, generally softwood pallets are used for import purpose because they're heights in weight. These types of rustic pallets are ideal for packing and exporting goods. These pallets are heat treated and are veritably light in weight.

Recycling of wood isn't only salutary for terrain but also bring effective for wood assiduity. It helps to save trees

and help to clean the terrain. Global warming is a term nearly everyone is familiar with. Global warming refers to the gradational rise in the overall of the temperature of the atmosphere of the Earth. There are various conditionings taking place which have been adding the temperature gradationally. Global warming is melting our ice glaciers fleetly. This is extremely dangerous to the earth as well as humans. The first step in working any problem is relating the cause of the problem. Thus, we need to first understand the causes of global warming that will help us do further in working it. In this essay on Global Warming, we will see the causes and results of Global Warming. Deforestation is also leading to warmer temperatures. The hazard of global warming is continuously causing major damage to the Earth's terrain. Utmost people are still ignorant of global warming and don't consider it to be a big problem in times to come. We're formerly passing some of its withering goods. It's and will oppressively affect ecosystems and disturb ecological balance.

REFERENCES

- Alessio B (2019). Resource quality of wood waste: The importance of physical and chemical impurities in wood waste for recycling. *Waste. Manage.* 87 (4):135-147.
- Koyano S, Ueno D, Yamamoto T, Kajiwara N (2019). Concentrations of POPs based wood preservatives in waste timber from demolished buildings and its recycled products. *Waste. Manage.* 85(1): 445-451.
- Wang L, Chen SS, Tsang DC, Poon CS, Shih K (2016) Recycling of construction waste wood into noise and thermal insulating cement-bonded particleboards. *Constr. Build. Mater.* 125 (2): 316-325.
- Welling Johannes (2015). Substitution potentials of recycled HDPE and wood particles from post-consumer packaging waste in Wood-Plastic Composites. *Waste. Manage.* 46(5):76-85.
- Zhou Xiaoyan (2020). Recycling waste plastic bags: From improving interfacial adhesion with wood towards fabricating formaldehyde-free plywood. *J. Clean. Prod.* 269(4):451-459.